

FTT-301 热套热电偶（阻）



产品名称: 热套热电偶/热电阻

产品说明:

1、应用

适合于蒸汽管道、锅炉及其他对温度、压力、流速有所要求的场所。

2、主要技术参数

电气出口: M20x1.5,NPT1/2

连接尺寸: M20x1.5,NPT1/2

防护等级: IP65

3、型号及规格(<http://www.fx-sensor.com> 010-51295202)

型号	分度号	测温范围 °C	公称压力	流速	规格 LxI
WRN-01T WRN2-01T	K	0-800	≤ 30MPa	≤ 100m/s	—
WRE-01T WRE2-01T	E	0-600			
WZP-01T WZP2-01T	Pt100	-200-+500			
WRN-624 WRN2-624	K	0-800	≤ 30MPa	≤ 80m/s	绝缘式
WRE-624 WRE2-624	E	0-600			
WZP-624 WZP2-624	Pt100	-200-+500			
WRN-625 WRN2-625	K	0-800			接壳式

WRE-625 WRE2-625	E	0-600			
WRN-012T WRN2-012T	K	0-800	≤ 10MPa	—	440x230 640x430 840x630 1340x1130 2500x1200 640x430 3000x1500 3500x1700
WRE-012T WRE2-012T	E	0-600			
WZP-012T WZP2-012T	Pt100	-200-+500			
WRN-12AT WRN2-12AT	K	0-800			
WRE-12AT WRE2-12AT	E	0-600			
WZP-12AT WZP2-12AT	Pt100	-200-+500			
WRN-013T WRN2-013T	K	0-800	≤ 30MPa	≤ 100m/s	380x50 430x100 480x150
WRE-013T WRE2-013T	E	0-600			
WZP-013T WZP2-013T	Pt100	-200-+500			
WRN-014T WRN2-014T	K	0-800	≤ 10MPa	≤ 80m/s	280x50 330x100 380x150 430x200 480x250 530x300
WRE-014T WRE2-014T	E	0-600			
WZP-014T WZP2-014T	Pt100	-200-+500			
WRN-015T WRN2-015T	K	0-800	≤ 10MPa	—	280x50 330x100 380x150 430x200 480x250 530x300 580x350 630x400
WRE-015T WRE2-015T	E	0-600			
WZP-015T WZP2-015T	Pt100	-200-+500			